



Dual CYCLONIC Separation Cyclones by the Dust Director®

ALWAYS A CLEAN FILTER — NO CLOGGING — NO DIRTY FILTERS TO TOUCH, CLEAN OR REPLACE ~ EVER AGAIN!
The End of Suction Drop Without Stopping to Purge the Filter or Without Using Electronics!

With a DUST DIRECTOR® CYCLONE you'll *always* be working with a clean filter *regardless* of what you're extracting — from dry powders to water, sludge, hot mastics, fiberglass, etc. . . . **Collects WET or DRY at the SAME TIME!**

Without using electronic switches, sensors or touch control panels, 100% of the motors' power is dedicated to SUCTION - the motors' suction power is *NOT* shared OR reduced to pulse clean the HEPA cartridge filter AND it stays CLEAN!



Operating without electronics or manual filter pulsing, **Dual Cyclonic Separation with AIRFlow HEPA Filtration** *guarantees* "You'll always be working with a clean filter."

How Does DUAL CYCLONIC SEPARATION Work?

For every 100 lbs. of concrete dust contained in the collection tank, 1 tablespoon of powder will escape the cyclone and be captured by the Clean Extreme Collection Bag before it can reach the HEPA cartridge filter.

How Effective is DUAL CYCLONIC SEPARATION?

With twice the separation, smaller dust and dirt particles are dramatically removed from the airstream ~ **You May Never Have to Replace the HEPA Cartridge Filter — Plus the HEPA Filter is completely washable!**

Dust Director® CYCLONES maintain 100% Suction without using Electronics & with No Filters to Clog — **PLUS the Washable Pleated HEPA Cartridge Filter Stays Clean!** —

With their compact size, large wheels and swivel/locking casters, while specifically designed to extract large volumes of silica without suction loss during concrete grinding, sawing and shot blasting operations, a Dust Director® CYCLONE is well equipped for use in any industry or application requiring sustained suction performance with little or no operator intervention to clean the filter.

Motors Operate Cooler, Consume Less Energy & Last Considerably Longer
by "Always Having with a Clean Working Filter."

Seven (7) Models, 120 & 240 Volt with 2 & 3-Motors: Powerful Sustained Suction ▣ Versatility — Extract Dry, Wet, Hot Mastic Debris without Changing or Compromising the Filters ▣ Portable, Compact Sizes ▣ Individual On/Off Motor Switches — "You" control the how much suction is needed.

DP2400S **120 Volt 2-Motor Split Tank:** 1200W motors, 8.5A x 2, 260 CFM, 83" H2O, 2" Inlet Port, 2" x 25' hose, 27"w x 24"l x 62"h, 9 pc. Nozzle Kit, 24 Gallon HD Mobile *Tipping* Cart, Dust Yield: 150 lbs. **Price: \$2,590.00**

DP3900S **240 Volt 3-Motor Split Tank:** Same as above w/ 1300W motors, 5.1Amp x 3, 420 CFM, 97" H2O. **Price: \$2,990.00**



Industrial Contractors' Supplies

- Dust Director Division -

N. Huntingdon, PA 15642

412-824-6933 • DustDirector.com

DUST DIRECTOR® CYCLONES with Dual Cyclonic Separation — 5 Additional Models

C2400S

24 Gallon Tank ~ 120 Volt, 2-Motor



Voltage, Watts, Amperage: 120 Volt, 1200 watt motors, 8.5 Amp x 2 Motors

Airflow: 260 CFM

Static Pressure: 83 in H2O

Dust Collection Capacity: 150 lbs

Dust Hose Connection: 2" Inlet Port

Dimensions: 22"W x 24"D x 55"H

Included Equipment: 2" x 25' hose, 2" ID Smooth Soft Vinyl Hose Cuff, Standard Tipping Cart, Complete 9 pc Nozzle, Kit. Price: **\$1,890.00**

C2400M

MAXI-BAG ~ 120 & 240 Volt, 2 & 3-Motor

Voltage, Watts, Amperage: 120 Volt, 1200 watt motors, 8.5 Amp x 2 Motors

Airflow: 260 CFM

Static Pressure: 83 in H2O

Dust Collection Capacity: Unlimited lbs

Dust Hose Connection: 2" Inlet Port

Dimensions: 21"W x 22"L x 71"H

Included Equipment: 2" x 25' hose, 2" ID Smooth Soft Vinyl Hose Cuff, Compact Telescoping Cart, Complete 9 pc Nozzle Kit. Price: **\$3,590.00**



C2400M

Maxi-Bag 240 Volt Model: Identical to the above C2400M model but with (3) single-phase 220 volt motors, 1300 watt x 3, 5.1 Amp x 3, 420 CFM, 97" H2O. Price: **\$3,900.00**

C2400B

55 Gallon Barrel Head ~ 120 & 240 Volt, 2 & 3-Motor



CONVERTS A 55 GALLON DRUM INTO A LARGE CAPACITY WET/DRY VACUUM

Voltage, Watts, Amperage: 120 Volt, 1200 watt motors, 8.5 Amp x 2 Motors

Airflow: 260 CFM

Static Pressure: 83 in H2O

Tank: Separator Drum Adapter w/ Cyclone Neck. Plastic Bag can be used in the drum.

Dust Collection Capacity: 600 lbs

Dust Hose Connection: 2" Inlet Port

Weight: 70 lbs.

Dimensions: 25"W x 38"H

Included Equipment: 2" x 25' hose, 2" ID Smooth Soft Vinyl Hose Cuff, Complete 9 pc Nozzle Kit

Price: **\$2,190.00**

C2400B

Barrel Head 240 Volt Model: Identical to the above 120 volt C2400B but with (3) single-phase 220 volt motors, 1300 watt x 3, 5.1 Amp x 3, 420 CFM, 97" H2O. Price: **\$2,590.00**